INCH-POUND


W-C-596/88C 20 July 2001 SUPERSEDING W-C-596/88B 1 October 1987

FEDERAL SPECIFICATION SHEET

CONNECTOR, PLUG, ELECTRICAL, SPECIAL PURPOSE, CABLE OUTLET, GROUNDING, LOCKING, 2 POLE, 3 WIRE, 15 AMPERES, 250 VOLTS, 50/60 HERTZ

> The General Services Administration has authorized the use of this federal specification sheet by all federal agencies.

The complete requirements for procuring the connectors described herein shall consist of this document and the latest issue of W-C-596/GEN.



NOTES:

- 1. Dimensions are in inches.
- 2. Metric equivalents are given for general information only.
- 3. Undimensioned pictorials are for reference purposes only.

FIGURE 1. Configuration and dimensions.

FSC 5935 AMSC N/A 1 of 3

W-C-596/88C

REQUIREMENTS:

Design and configuration: See figure 1.

Dimensions: Shall conform to NEMA WD 6, configuration L6–15R.

Armored construction: Not acceptable.

Rating:

Voltage: 250 volts. Current: 15 amperes. Frequency: 50/60 hertz.

Mating connector: W-C-596/87 and W-C-596/89.

Strain relief: Accommodate cable diameter .300 - .575 inch.

Part or Identifying Number (PIN): W-C-596/88- (dash number from table I).

Supersession and cross reference: See table II.

TABLE I. Dash number.

Dash no.	Supersedes style	Description
1		Cable outlet

TABLE II. Supersession and cross reference.

Active Government PIN	Superseded numbers						
	CAGE 39317 <u>1</u> /	CAGE 79409	CAGE 74545	CAGE 71183	CAGE 04009	CAGE 81091	
W-C-596/88-1			4579-C 4579-CY		6555 6566	4580	

^{1/} CAGE is the Commercial and Government Entity code which is assigned and maintained by Defense Logistics Information Service (DLIS) in Battle Creek, MI.

W-C-596/88C

MILITARY INTERESTS:

Custodians
Army - CR
Navy - YD
Air Force - 11
DLA - CC

Review Activities

Army - AV, CR4, MI Navy - AS, EC, MC, SH Air Force - 99

CIVIL AGENCY COORDINATING ACTIVITIES:

DCGOVT - DCG DOT - ACO GSA - 7FXE HHS - FEC USDA - AFS

Preparing Activity: DLA - CC

(Project 5935-4305-40)